


Next-Generation Model-based Variability Management: Languages and Tools

Mathieu Acher (Associate Professor, Rennes)

Patrick Heymans (Professor, Namur / Lille)

Philippe Collet (Associate Professor, Nice)

Philippe Lahire (Professor, Nice)

Acknowledgments

- Colleagues at University of Namur
 - Raphaël Michel, Quentin Boucher, Ebrahim Abbasi, Arnaud Hubaux (PhD), Gilles Perrouin (PhD), Assoc. Prof. Anthony Cleve
- Contributors of FAMILIAR
 - Robert B. France (Colorado State University)
 - Students
 - Aleksandar Jakšić (Colorado State University)
 - Foudil Bendjabeur (Université Nice Sophia Antipolis)
 - Master students in Namur (variability management course)

Audience

- No pre-requisite background!
- Targeted Audience
 - Academics or practitioners
 - **Curious guys**: e.g., PhD students or modellers unaware of...
 - Variability and software product lines (SPLs)
 - Variability modelling
 - Configuration
 - **MDE guys**: people involved or interested in the development of model management tools
 - e.g., model composition/decomposition
 - **SPL guys**: advances that want to learn new technique

At the end of the tutorial...


- You will have an overview of what's going on in the field of variability and model-based software product line engineering
- You will be able to go further with the languages and modelling techniques
 - so to reuse them in practical or academic contexts
- **Supporting material:** <https://nyx.unice.fr/projects/familiar/wiki/MODELS12-tutorial>
 - slides of the tutorial
 - related articles,
 - TVL models,
 - FAMILIAR scripts,
 - and packaged tools to interactively play with the models during the tutorial.

Plan

- Why managing **Variability** does matter (30')
- **Modelling** variability with TVL (60')
- **Managing** variability models with FAMILIAR (90')

```
root PloneMeeting {
  group allof {
    General,
    Data,
    WorkflowSec,
    Interface,
    Email,
    Tasks,
    Advices,
    Votes
  }
}


General {
  group allof {
    Title,
    opt DefaultAssembly,
    opt DefaultSignatures,
    LinkedFolder,
    opt IsDefault,
    NumberLastItemLastMeeting {
      int number;
    },
    opt NumberLastMeetingConfig {
      int number;
    },
    opt MeetingConfigID
  }
}
```



Why managing **Variability** does (and will) matter



Software-intensive systems



come in many variants



This image may contain optional equipment.



Agila, Club

1.2i 16v, 5 Speed

Blaze Red, Melt / Elba Charcoal

Total

€ 15,684.00

1. Trims/Series

2. Engine/Transmission

3. Colour & Style

4. Options

5. Summary

Next Step

Choose Your Options

Audio/Comms/Nav Heating/Ventilation Mechanical Safety/Security A-Z

Audio/Comms/Nav

- ☒ **CD 30** **Standard**
- MP3 CD player with MP3 format, stereo radio, steering wheel mounted audio controls

Heating/Ventilation

- ☒ **Air conditioning** **€ 923.00**

Mechanical

- ☒ **Electronic Stability Programme (ESP)** **€ 411.00**

Safety/Security

- ☒ **Emergency tyre inflation kit in lieu of space-saver spare wheel and tyre** **Standard**

Audio/Comms/Nav Heating/Ventilation Mechanical Safety/Security A-Z

Next Step: Summary

Legend

- ☒ Selected Option
- ☐ Selectable Option
- ☒ Option contained in an option pack
- ☐ Option contained in an option pack or standard equipment which has been replaced by another option
- ☐ Option that is only selectable together with another option. Please click for details

Pricing Details

Club € 14,350.00

1.2i 16v, 5 Speed

Blaze Red € 0.00

Melt / Elba Charcoal € 0.00

15-inch steel wheels with 185/60 € 0.00

R 15 tyres and flush wheel covers

Options (2) -



You selected:

☒ Air conditioning € 923.00


☒ Electronic Stability Programme (ESP) € 411.00

Total € 15,684.00


Linux Kernel




Database
Engine



Printer
Firmware



Features in Microsoft Office



Variability

“the ability of a system to be efficiently extended, changed, customized or configured for use in a particular context”

Mikael Svahnberg, Jilles van Gurp, and Jan Bosch (2005)



httpd.conf -- win32 Apache

Building a Web Server, for Windows

```
Listen 80
ServerRoot "/www/Apache2"
DocumentRoot "/www/webroot"
```

```
ServerName localhost:80
ServerAdmin admin@localhost
```

```
ServerSignature On
ServerTokens Full
```

```
DefaultType text/plain
AddDefaultCharset ISO-8859-1
```

```
UseCanonicalName Off
```

```
HostnameLookups Off
```




```
ErrorLog logs/error.log
LogLevel error
```

```
PidFile logs/httpd.pid
```

```
Timeout 300
```

```
KeepAlive On
MaxKeepAliveRequests 100
KeepAliveTimeout 15
```

```
<IfModule mpm_winnt.c>
    ThreadsPerChild 250
    MaxRequestsPerChild 0
</IfModule>
```



If you're able to master variability...

- Reduce development costs
- Reduce certification costs
- Shorten time-to-market



- But, are you able?
 - developing, verifying, certifying **billions of variants** is challenging!




Variability = Complexity

33 optional, independent
features



a unique variant for every
person on this planet



320^{optional, independent} features

more variants than estimated
atoms in the universe



2000 features

10000 features



Automation?

Avoid solving the same problem!

2, 3...n times



Correctness?

A problem has been detected and windows has been shut down to prevent damage to your computer.

PAGE_FAULT_IN_NONPAGED_AREA

If this is the first time you've seen this Stop error screen, restart your computer. If this screen appears again, follow these steps:

Check to make sure any new hardware or software is properly installed. If this is a new installation, ask your hardware or software manufacturer for any windows updates you might need.

If problems continue, disable or remove any newly installed hardware or software. Disable BIOS memory options such as caching or shadowing. If you need to use Safe Mode to remove or disable components, restart your computer, press F8 to select Advanced startup options, and then select Safe Mode.

Technical information:

*** STOP: 0x00000050 (0x800005F2, 0x00000000, 0x804E83C8, 0x00000000)

Beginning dump of physical memory
Physical memory dump complete.

Contact your system administrator or technical support group for further assistance.




**Maintenance?
Comprehension?**

Why managing **Variability** does (and will) matter

Goal: Software mass customization
/ Adaptive and configurable systems




Problem: **Variability = Complexity**



Approach: **Model-based variability management**





Software-intensive systems
come in many variants





Model-based
Variability Management

Domain Engineering




Application Engineering




« the investments required to develop the reusable artifacts during **domain engineering**, are outweighed by the benefits of deriving the individual products during **application engineering** »

Jan Bosch et al. (2004)




**99% domain engineering,
1% application engineering?**

- specifies what you want (click, click, click) a customized product is automatically built for you
- Iterate the process for n products




Variability Model




Main Artefacts (e.g., source code)

Modeling
variability
is crucial



Configuration



Software Generator

Unused flexibility



Illegal variant



Variability Model

Feature Model: *de facto* standard

- Research
 - 2500+ citations of [Kang et al., 1990] on Google Scholar
 - Central to many generative approaches
 - at requirements or code level
 - Tools & Languages (GUIDSL/FeatureIDE, SPLOT, FaMa, etc.)
- Industry
 - Tools (Gears, pure::variants),
 - Will be Part of Common Variability Language (CVL), future OMG standard

Plan

- W
- M
- M
- Configuring fea

g Variability does matter

iability with TV/L

th FAMILIAR

```

root PloneMeeting {
  group allof {
    General,
    Data,
    WorkflowSec,
    Interface,
    Email,
    Tasks,
    Advices,
    Votes
  }
}


General {
  group allof {
    Title,
    opt DefaultAssembly,
    opt DefaultSignatures,
    LinkedFolder,
    opt IsDefault,
    NumberLastItemLastMeeting {
      int number;
    },
    opt NumberLastMeetingConfig {
      int number;
    },
    opt MeetingConfigID
  }
}
    
```

```

// PloneMeeting: example
fmGeneral = FM ("general.fml")
fmData = FM ("data.fml")
csts = constraints (Classifier -> IsDefault ; Tags -> DefaultAssembly ; )

// composition
fmPlone = aggregate { fmGeneral fmData } withMapping csts
// decomposition
fmGeneralBis = slice fmPlone including fmGeneral.*

cmp = compare fmGeneralBis fmGeneral // Impact of constraints?
convert fmGeneralBis into S2T2 // or FeatureIDE, TVL, SPLOT, etc.
    
```



SPLIT - Software Product Line Online Tools

http://www.splot-research.org/

SPLIT - Software Product Line O...

View Options

View List: User Visualization: ☒ pruned ☐ collapsed

Plone Meeting (57 features)

Configuration Steps [next]					
39%					
Step	Decision	#Decisions (outgoing)	#Propagations (outgoing)	#SAT checks (outgoing)	SAT time (outgoing)
1	Meeting Config	14 (24.4%)	13	21	2 ms
2	Category order	17 (29.8%)	2	9	1 ms
3	Decided	18 (31.4%)	0	7	1 ms
4	Archived	19 (33.3%)	0	7	0 ms
5	Created	20 (35.1%)	0	7	1 ms
6	Closed	21 (36.8%)	0	7	0 ms
7	Published	22 (38.6%)	0	7	0 ms


```

root PloneMeeting {
  group allof {
    General,
    Data,
    WorkflowSec,
    Interface,
    Email,
    Tasks,
    Advices,
    Votes
  }
}

General {
  group allof {
    Title,
    opt DefaultAssembly,
    opt DefaultSignatures,
    LinkedFolder,
    opt IsDefault,
    NumberLastItemLastMeeting {
      int number;
    },
    opt NumberLastMeetingConfig {
      int number;
    },
  },
  opt MeetingConfigID
}

```

The screenshot shows the FAMILIAR IDE with a textual model on the left and a graphical feature diagram on the right. The textual model defines a 'PloneMeeting' product with various features and constraints. The graphical model shows a hierarchy of features, with 'General' and 'Data' as main components. A console at the bottom shows the output of the model analysis.

```

// PloneMeeting: example
fmGeneral = FM ("general.fml")
fmData = FM ("data.fml")
csts = constraints (Classifier -> IsDefault ; Tags -> DefaultAssembly ; )

// composition
fmPlone = aggregate { fmGeneral fmData } withMapping csts
// decomposition
fmGeneralBis = slice fmPlone including fmGeneral.*

cmp = compare fmGeneralBis fmGeneral // impact of constraints?
convert fmGeneralBis into S2T2 // or FeatureIDE, TVL, SPLOT, etc.

```

The screenshot shows the SPLOT web interface. On the left, there are 'View Options' for 'User' and 'Visualization' (pruned, collapsed). The main area displays 'Plone Meeting (57 features)' with a tree view of features. On the right, a table shows 'Configuration Steps' with columns for Step, Decision, #Decisions (cumulative), #Propagations (at step), #SAT checks (at step), and SAT time (at step).

Step	Decision	#Decisions (cumulative)	#Propagations (at step)	#SAT checks (at step)	SAT time (at step)
1	Meeting Config	14 (24.6%)	13	21	2 ms
2	Category order	17 (29.8%)	2	9	1 ms
3	Decided	18 (31.6%)	0	7	1 ms
4	Archived	19 (33.3%)	0	7	0 ms
5	Created	20 (35.1%)	0	7	1 ms
6	Closed	21 (36.8%)	0	7	0 ms
7	Published	22 (38.6%)	0	7	0 ms

Formally define the scope of your product line with a textual language

Edit, compose, decompose, compare, reason about your variability specifications

Configure your product line with a collaborative, distributed and dependable feature-based configuration



Modelling variability with TVL

(Text-based Variability Language)



R8 Spyder 5.2 FSI quattro R tronic

Prix total

171.216,00 EUR

Prix de base

170.490,00 EUR

Equipements optionnels

726,00 EUR

- ▶ Informations détaillées
- ▶ Entrez l'Audi Code **8**
- ▶ Générer un PDF
- ▶ Nouvelle configuration



[+] Plein écran / Dimensions ▶ Fermer la capote ☒ Habillage ☐ Tableau de bord

Packs

Aucun pack n'est proposé pour ce modèle.

Couleurs

Blanc Ibis

Noir

Prix: 0,00 EUR



Couleurs métallisées à partir de 0,00 EUR



Couleurs à effet perlé à partir de 0,00 EUR



Couleurs personnalisées Audi exclusive

Audi exclusive

Couleur capote

Noir



Jantes

4 Jantes alu 5 BRANCHES ROTOR finition titane 8,5 x 19 à l'avant, 11 x 19 à l'arrière. Pneus 235/35 R19 à l'avant et 305 /30 R19 à l'arrière
Prix: 726,00 EUR

19" à partir de 0,00 EUR





R8 Spyder 5.2 FSI quattro R tronic

Prix total

185.899,35 EUR

Prix de base

170.490,00 EUR

Équipements optionnels

15.409,35 EUR

- ▶ Informations détaillées
- ▶ Entrez l'Audi Code
- ▶ Générer un PDF
- ▶ Nouvelle configuration



[+] Plein écran / Dimensions [▲] Vue extérieure [▶] Tableau de bord

- ▶ Packs d'équipements
- ▶ Extérieur
- ▶ Jantes & pneumatiques
- ▶ Intérieur
- ▶ Volants
- ▶ Sièges
- Sécurité & technique**
- ▶ Infotainment

- ▶ Châssis
- ▶ Freins
- Systèmes d'assistance**
- ▶ Autres

excludes

☒	Régulateur de vitesse		320,65 EUR
☐	Système d'aide au stationnement APS avant / arrière		931,70 EUR
☐	Système d'aide au stationnement APS avant / arrière avec affichage dans l'écran MMI		1.373,35 EUR
☒	Système d'aide au stationnement Advanced : APS avant et arrière et caméra arrière		1.790,80 EUR
☒	Audi hill assist : assistance au démarrage en côte		Série

[+] Réinitialiser la sélection

Attention:
Le prix peut varier en fonction du choix de moteur et des équipements.

Un aperç des équipements:

Mode expert

A5 Sportback 3.0 TDI quattro S tronic

Prix total

54.460,15 EUR

Prix de base

50.570,00 EUR

Équipements optionnels

3.890,15 EUR

- Informations détaillées
- Entrez l'Audi Code 
- Nouvelle configuration

Vérification de votre sélection

Cet équipement nécessite un équipement complémentaire:

- | | | |
|--|---|--------------|
| ☒ GPS Plus avec disque dur |  | 2.934,25 EUR |
|--|---|--------------|

Voici les équipements complémentaires possibles:

- | | | |
|---|---|------------|
| ☐ Ordinateur de bord en couleur avec programme efficiency |  | 181,50 EUR |
|---|---|------------|

Remarque: uniquement sur les modèles avec système Start-Stop et uniquement disponible en combinaison avec l'autoradio Concert, l'autoradio Symphony ou un système de navigation

- | | | |
|---|---|--------------|
| ☐ Pack Intenso Plus |  | 3.100,00 EUR |
|---|---|--------------|

☐ Sans appareil de navigation

2.934,25 EUR

Série

[+] Plein écran / Dimensions

▸ Packs d'équipements

- Extérieur
- Jantes & pneumatiques
- Intérieur
- Volants
- Sièges
- Sécurité & technique

Infotainment

Attention:

Le prix peut varier en fonction du choix de moteur et des équipements.

Un aperçu des équipements:

Mode expert

 Réinitialiser la sélection

1 Modèle

2 Moteur

3 Extérieur

4 Intérieur


5 Option

6 Votre Audi



Français

Suivant ▸

Feature Models




Feature Models (Background)





Hierarchy: rooted tree

Variability:

- mandatory,
- optional,
- Groups: exclusive or inclusive features
- Cross-tree constraints







Hierarchy + Variability
 =
set of valid configurations

configuration = set of features selected

{CarEquipment, Comfort, DrivingAndSafety, Healthing, AirConditioning, FrontFogLights}







Hierarchy + Variability
 =
set of valid configurations

configuration = set of features selected

{CarEquipment, Comfort, DrivingAndSafety, Healthing, AirConditioning}







Hierarchy + Variability
 =
set of valid configurations

configuration = set of features selected

{CarEquipment, Comfort, DrivingAndSafety, Healthing, AirConditioning, AirConditioningFrontAndRear, FrontFogLights}







Hierarchy + Variability
 =
set of valid configurations

configuration = set of features selected

{CarEquipment, Comfort, DrivingAndSafety, Healthing, AirConditioning, AutomaticHeadLights}






Hierarchy + Variability
 =
set of valid configurations




{CarEquipment, Comfort,
DrivingAndSafety,
Healthing}



{AirConditioning, FrontFogLights}
 {AutomaticHeadLights, AirConditioning, FrontFogLights}
 {AutomaticHeadLights, FrontFogLights, AirConditioningFrontAndRear}
 {AirConditioningFrontAndRear}
 {AirConditioning}
 {AirConditioningFrontAndRear, FrontFogLights}

Feature Models



▼ CarEquipment

▼ ● Healinging

▼ A

AirConditioningFrontAndRear

AirConditioning

▼ ● Comfort

○ AutomaticHeadLights

▼ ● DrivingAndSafety

○ FrontFogLights

▼ Constraints

AutomaticHeadLights $\Rightarrow$ FrontFogLights


The screenshot displays the Audi website for the R8 Spyder 5.2 FSI quattro R tronic. It shows various configuration options and their associated costs.


Option	Price
Packs d'équipements	
Exterieur	
Jantes & pneumatiques	
Intérieur	
Volants	
Séjour	
Sécurité & technique	
Intégration	
Régulateur de vitesse	320,65 EUR
Système d'aide au stationnement APS avant / arrière	931,70 EUR
Système d'aide au stationnement APS avant / arrière avec affichage dans l'écran info	1.373,35 EUR
Système d'aide au stationnement Advanced / APS avant et arrière et caméra arrière	1.790,80 EUR



Attention: Si vous choisissez une option, vous devez également choisir une option de base. Un aperçu des équipements: Mode expert

1 Mobile 2 Moteur

44







Visualisation will help, right ?

- Tools create their own problems
- Lock-in, dependance
- Some information is inevitably textual
 - OCL constraints in UML
 - Minispecs in StateCharts
 - Attributes and constraints in FD

Why not use text altogether ?

- There are powerful tools for that
- Helps with
 - Editing
 - Transformation
 - Versioning
 - Information exchange
 - ...
- Graphical views can be generated anyway

Not a new idea


Language	User Friendly	Attributes	Cardinalities	Cross tree constraints	Modularisation
Van Deursen et al.	✓				
GUIDSL (AHEAD)	✓				
SXFM	✓				
XML-based (FAMA etc.)		✓	✓	✓	

+ CML
+ VSL


Furthermore

- Intuitive C-like syntax
- Formal semantics
- Statically typed
- Implemented


TVL : allOf – and decomposition




TVL : optional features




TVL : one of – xor decomposition




TVL : someOf – or decomposition



TVL : Cardinalities



TVL : Attributes



TVL : Constants

```
const int minSize is 17;  
const int maxSize is 19;
```

```
Exterior {  
  group allof {  
    Wheels {  
      int size in [minSize..maxSize]  
    }  
  }  
}
```

constants can be reused

constants are allowed in cardinalities, expressions, etc.

TVL : Attributes

```
Car {  
  int price is sum(children.price);  
}
```

aggregation function

aggregation functions : sum, mul, min, max


```
Equipment {  
  int price is sum(selectedChildren.price);  
}
```

built-in selectors

```
  group someof {  
    NavigationSystems {  
      int price is 605;  
    },  
    Telephone {  
      int price is 300;  
    },  
    Speakers {  
      int price is 690;  
    },  
    Other {  
      int price is 385;  
    }  
  }
```

```
}
```

TVL : Attributes



TVL : ifIn / ifOut

```
Infotainment {  
  group someof {  
    NavigationSystem {  
      int price;  
      group oneof {  
        DVDBased {  
          ifIn: NavigationSystem.price == 1620;  
        },  
        HDDBased {  
          ifIn: NavigationSystem.price == 2045;  
        }  
      }  
    },  
    ...  
  }  
}
```

conditional constraint

ifIn : applies only if the feature is selected

ifOut : applies if the feature is not selected

TVL : Ternary operator

condition
a feature is true if it is selected

```
Infotainment {  
  group someof {  
    NavigationSystem {  
      int price = DVDBased ? 1620 : 2045;  
      group oneof {  
        DVDBased,  
        HDDBased  
      }  
    },  
    ...  
  }  
}
```

value if condition
is false

value if condition
is true

TVL : Modularity

```
root Car {  
    group allOf {  
        BodyStyle,  
        Model,  
        Engine,  
        Equipment }  
}
```

```
include(BodyStyle.tvl);  
include(Model.tvl);  
include(Engine.tvl);  
include(Equipment.tvl);
```



Split model in reusable parts
using external files

TVL : Modularity

BodyStyle.tvl

```
BodyStyle {  
  group oneof {  
    Avant,  
    Door3,  
    Sportback,  
    Coupe,  
    Cabriolet,  
    Roadster,  
    Spyder,  
    SUV  
  }  
}
```

Model.tvl

```
Model {  
  group oneof {  
    A1,  
    A3,  
    S3,  
    A4,  
    S4,  
    A5,  
    S5,  
    RS5,  
    A6,  
    A7,  
    A8,  
    A8L,  
    R8  
    Q3,  
    Q5,  
    Q7,  
    TT,  
    TTS,  
    TT RS  
  }  
}
```

Engine.tvl

```
Engine {  
  group oneof {  
    SE12TFSI,  
    CE14TFSI,  
    CE14TFSI119,  
    Sport12TFSI,  
    Sport14TFSI,  
    Sport14TFSI119,  
    BlackEdition14TFSI,  
    SLine12TFSI,  
    SLine14TFSI,  
    SE16TDI,  
    CE16TDI,  
    CE20TDI,  
    ...  
  }  
}
```

TVL : Tools


- Key references
 - Classen, A.; Boucher, Q. and Heymans, P. A Text-based Approach to Feature Modelling: Syntax and Semantics of TVL. In Science of Computer Programming (SCP), Special Issue on Software Evolution
 - Hubaux, A.; Boucher, Q.; Hartman, H.; Michel, R. and Heymans, P. Evaluating a Text-based Feature Modelling Language: Four Industrial Case (SLE 2010)
 - <http://info.fundp.ac.be/tvl/>
- Support
 - Parser / Syntactic and semantic checker
 - SAT-based checker for Boolean models
- Ongoing
 - SMT-based checker for models with numerical attributes (ongoing)
 - Eclipse editor (ongoing)

Managing variability models with FAMILIAR


At the end of the tutorial (bis)

- You will have an overview of what's going on in the field of variability and model-based software product line engineering
- You will be able to go further with the languages and modelling techniques
 - reuse them in practical or academic contexts
- **Supporting material:** <https://nyx.unice.fr/projects/familiar/wiki/MODELS12-tutorial>
 - slides of the tutorial
 - related articles,
 - TVL models,
 - FAMILIAR scripts,
 - and packaged tools to interactively play with the models during the tutorial.

#1 Automated Analysis



#2 Multiple Feature Models



The screenshot shows the Audi R8 Spyder configuration website. It includes images of the car from the outside and inside. The configuration options and prices are as follows:


Option	Price (EUR)
R8 Spyder 5.2 FSI quattro R tronic	185.899,35
Prix total	185.899,35
Prix de base	170.490,00
Equipements optionnels	15.409,35

Additional options and prices:

- Régulateur de vitesse: 320,65 EUR
- Système d'aide au stationnement APS avant / arrière: 931,70 EUR
- Système d'aide au stationnement APS avant / arrière avec affichage dans l'écran MMI: 1.373,35 EUR
- Système d'aide au stationnement Advanced: APS avant et arrière et caméra arrière: 1.790,80 EUR

The website also shows a list of optional equipment and a 'Suivant' button.

Two Key Requirements



- **#1 Automated analysis**

- Aka support to better understand and play with your feature model (TVL model)


Automated analysis of feature models 20 years later:
A literature review ☆

David Benavides *, Sergio Segura, Antonio Ruiz-Cortés

- **#2 Managing multiple feature models**

- Composing / Decomposing / Diff and Reasoning about their relationships
- Combining these operators


FAMILIAR language and environment




```
// foo.fml
fm1 = FM ("foo1.tvl")
fm2 = FM ("foo2.m")
fm3 = merge intersection { fm1 fm2 }
c3 = counting fm3
renameFeature fm3.TV as "OutputTV"
fm5 = aggregate { fm3 FM ("foo4.xml") }
assert (isValid fm5)
fm6 = slice fm5 including fm5.TV.*
export fm6
```



FAMILIAR





True/False
8759
"OutputTV", "TV"



Interoperability

Language facilities

Environment



FAMILIAR ... features

```
fm1 = FM("foo.tvl")
fm2 = FM ("foo.m")
fm3 = FM ("foo.xmi")
fm4 = FM (A : B ....)
```

Interoperability

serialize fm4 into SPLOT
serialize fm1 into featureide

isValid
compare

counting

configs

cores

deads

configuration

select
deselect
asFM

Reasoning

falseOptionals
cleanup

merge
diff
intersection
union

insert

De/Composition

aggregate

map
unmap

extract

slicing

renameFeature
removeFeature
accessors
copy

Editing

setOptional
setMandatory
setAlternatives
setOr

fm1.*
fm1.B
iterator/conditional
assertion

Language Facilities

modular mechanisms

restricted set of types

Hello World


```
fm1 = FM ("foo1.tv1")
```

```
s = "hello world"
```

```
c = counting fm1
```

```
n = size fm1.*
```

```
println s
```



```
MacBook-Pro-de-Mathieu-2:FML-scripts macher$ java -jar -Xmx1024M ../FML-0.9.9.6.jar helloworld.fml
hello world
```

```
FAMILIAR (for FeAture Model scrIPt Language for manIpulation and Automatic Reasoning) version 0.9.9.6 (beta)
University of Nice Sophia Antipolis, UMR CNRS 6070, I3S Laboratory
https://nyx.unice.fr/projects/familiar/
fml> ls
(DOUBLE) c
(FEATURE_MODEL) fm1
(INTEGER) n
(STRING) s
fml> █
```

Typed language

- Domain-specific types
 - Feature Model,
 - Configuration,
 - Feature,
 - Constraint

```
fm1 = FM ("foo1.tv1")  
ft1 = root fm1  
ft2 = fm1.B  
fts = fm1.*  
n = size fts  
n2 = cores fm1
```

- Other types include
 - Set
 - String
 - Boolean,
 - Enum,
 - Integer and Real.

```
cf = configuration fm1  
select B in cf  
deselect C in cf
```

```
cst1 = constraint (B -> !C)  
addConstraint cst1 to fm1
```

- A set of operations, called **operators**, are defined for a given type.

Typed language


```
fm1 = FM ("foo1.tv1")
ft1 = root fm1
ft2 = fm1.B
fts = fm1.*
n = size fts
n2 = cores fm1

cf = configuration fm1
select B in cf
deselect C in cf

cst1 = constraint (B -> !C)
addConstraint cst1 to fm1
```

```
fm1> ls
(FEATURE_MODEL) fm1
(SET) fts
(FEATURE) ft2
(CONSTRAINT) cst1
(INTEGER) n
(CONFIGURATION) cf
(SET) n2
(FEATURE) ft1
```


Typed language




```
fm1 = FM ("foo1.tv1")
ft1 = root fm1
ft2 = fm1.B
fts = fm1.*
n = size fts
n2 = cores fm1

cf = configuration fm1
select B in cf
deselect C in cf

cst1 = constraint (B -> !C)
addConstraint cst1 to fm1
```

```
fml> ft1
ft1: (FEATURE) A
fml> ft2
ft2: (FEATURE) B
fml> fts
fts: (SET) {G;E;D;F;C;A;B}
fml> n
n: (INTEGER) 7
fml> n2
n2: (SET) {E;A;B}
fml> cf
cf: (CONFIGURATION) selected: [E, A, B]      deselected: [C]
fml> cst1
cst1: (CONSTRAINT) (B -> !C)
fml> fm1
fm1: (FEATURE_MODEL) A: [D] B E [C] ;
E: (F|G) ;
(B -> !C);
```

Importing/Exporting feature models



Internal notation *or* by “filename extensions”

```
fm1 = FM ( "foo1.tvl" )
```

```
fm2 = FM ( A : [B] [C] D ; )
```

```
fm3 = FM ( "foo2.m" )
```

```
serialize fm2 into SPLOT // export
```

Feature Accessors (1)

```
fm1 = FM (A : B [C] ; B : E F ; C : (I|J) ; )
```

```
r1 = root fm1
```

```
s = children r1
```

```
s1 = children fm1.A
```

```
assert (s eq s1) // equality of the two sets
```

```
ft1 = parent fm1.F
```

```
str1 = name ft1
```


```
ft2 = parent F // parent fm1.F
```

```
// another FM
```

```
fm2 = FM (A : B C E ; C : (I|J)+ ; )
```

```
ft3 = fm2.B
```

```
ft4 = name B // ambiguity
```



Other constructs

```
fm1 = FM (A: B [C] D; D : (E|F)+; F : (I|J|K); E : [Z]; )
```

```
fm1bis = copy fm1 // save the original version
```

```
renameFeature fm1.B as "Bbis"
```

```
s1 = fm1.* // set of features of fm1
```

```
foreach (ft1 in s1) do
```

```
    println ft1
```

```
end
```

```
acher-scr:FML-scripts macher$ java -jar -Xmx1024M ../FML-0.9.9.5.jar ftAccessors2.fml  
Bbis
```

```
D
```

```
E
```

```
A
```

```
Z
```

```
I
```


```
C
```

```
J
```

```
K
```

```
F
```


```
FAMILIAR (for FeAture Model scrIPt Language for manIpulation and Automatic Reasoning) version 0.9.9.5 (bet  
University of Nice Sophia Antipolis, UMR CNRS 6070, I3S Laboratory  
https://nyx.unice.fr/projects/familiar/  
fml> exit  
Bye, FAMILIAR user!
```



Configuration


```
fml = FM (A: B [C] [D] E; D : (F|G) ; E : (I|J|K|L) ; C -> !D ; )
c1 = configuration fml
select C in c1
sc1 = selectedF c1 // accessors
cFM1 = asFM c1 // configuration and FM: back!
```

```
MacBook-Pro-de-Mathieu-2:FML-scripts macher$ java -jar -Xmx1024M ../FML-0.9.9
FAMILIAR (for FeAture Model scrIpT Language for manIpulation and Automatic Re
University of Nice Sophia Antipolis, UMR CNRS 6070, I3S Laboratory
https://nyx.unice.fr/projects/familiar/
fml> cFM1
cFM1: (FEATURE_MODEL) A: B E C ;
E: (J|L|I|K) ;
E;
A;
B;
C;
fml> fm1
fm1: (FEATURE_MODEL) A: [D] B E [C] ;
D: (F|G) ;
E: (J|L|I|K) ;
(C -> !D);
```



Operations for Feature Models (1)

```
fm1 = FM (A : [B] [C] ; B -> !C ; B and C ; )  
b1 = isValid fm1
```




```
acher-scr:FML-scripts macher$ java -jar -Xmx1024M ../FML-0.9.9.5.jar operatorsFM.fml  
FAMILIAR (for FeAture Model scrIpt Language for manIpulation and Automatic Reasoning)  
University of Nice Sophia Antipolis, UMR CNRS 6070, I3S Laboratory  
https://nyx.unice.fr/projects/familiar/  
fml> ls  
(FEATURE_MODEL) fm1  
(BOOLEAN) b1  
fml> b1  
b1: (BOOLEAN) false  
fml> configs fm1  
res0: (SET) {}
```



Operations for Feature Models (2)

```
1 fm1 = FM (W : P (T|U); P : (R|S)+ ; T : [V] [A] ; R -> !V ; S -> U ; R -> A ; )
2 b1 = isValid fm1
3 s1 = configs fm1
4 c1 = counting fm1
5 dfm1 = deads fm1
6 println "cores: ", cores fm1
7 fo1 = falseOptionals fm1
```



ar operatorsFM2.fml

Automatic Reasoning)

φ


```
acher-scr:FML-scripts macher$ java -jar -Xmx1024M fam.jar operatorsFM2.fml
cores: {P;W}

FAMILIAR (for FeAture Model scrIPt Language for
University of Nice Sophia Antipolis, UMR CNRS 6004
https://nyx.unice.fr/projects/familiar/)
fml> ls
(SET) fo1
(SET) dfm1
(SET) s1
(DOUBLE) c1
(BOOLEAN) b1
(FEATURE_MODEL) fm1
fml> c1
c1: (DOUBLE) 2.0
fml> fo1
fo1: (SET) {A}
fml> dfm1
dfm1: (SET) {V}
```

Operations for Feature Models (3)

```
fm1 = FM (A : [B] [C] ; B -> !C ; B and C ; )
b1 = isValid fm1
```

```
csts1 = constraints fm1
foreach (cst in csts1) do
    println "removing constraint... ", cst
    removeConstraint cst in fm1
    c = counting fm1
    println "now the number of valid configurations is... ", c
end
```



```
MacBook-Pro-de-Mathieu-2:FML-scripts macher$ java -jar -Xmx1024M ../FML-0.9.9.5.jar operatorsFM3.fml
removing constraint... (B & C)

now the number of valid configurations is... 3.0


removing constraint... (B -> !C)

now the number of valid configurations is... 4.0
```

Multiple Feature Models

SPL/internal/software variability

(Pohl et al. 2005, Metzger 2007)



PL/external variability

(Pohl et al. 2005, Metzger 2007)

Concern 1, 2, 3, ..., n

View 1, 2, 3, ..., n


(Dunghana et al. 2010,
Hubaux et al. 2010, Zaid et al. 2010)

context variability

(FORM 1998, Tun et al. 2009 (problem world),
Hartmann 2008 (CVM), Lee et al. 2010)

Stakeholder 1, 2, 3, ..., n

(Czarnecki 2005, Reiser et al. 2007,
Hartmann et al. 2009, Classen et al. 2009,
Mendonca et al. 2010)



SoC support = Composition/Decomposition
for managing
large, complex and multiple
feature models

FORM 1998, Tun et al. 2009 (SPLC), Hartmann 2008 (SPLC), Lee et al. 2010, Czarnecki 2005, Reiser et al. 2007 (RE journal), Hartmann et al. 2009 (SPLC), Thuem et al. 2009 (ICSE), Classen et al. 2009 (SPLC), Mendonca et al. 2010 (SCP), Dunghana et al. 2010, Hubaux et al. 2011 (SoSyM), Zaid et al. 2010 (ER), She et al., 2011 (ICSE), etc.


Composing Feature Models (1)

```

fm1 = FM (A : B [C] [D] ; D : (E|F) ; C -> !E; )
fm2 = FM (I : J [K] L ; )
fm3 = FM (M : (N|O|P)+ ; )
cst = constraints (J implies N ; )

// equivalent to aggregate { fm1 fm2 fm3 }
fm4 = aggregate fm* withMapping cst

```



Composing Feature Models (2)

```
fm1 = FM (A : B [C] [D] ; D : (E|F) ; C -> !E; )
fm2 = FM (I : J [K] L ; )
fm3 = FM (M : (N|O|P)+ ; )
cst = constraints (J implies C ; )
```

```
// equivalent to aggregate { fm1 fm2 fm3 }
```

```
fm4 = aggregate fm* withMapping cst
```

```
// composition sometimes leads to "anomalies"
```

```
dfm4 = deads fm4
```


```
fm1 = FM (A : B [C] [D] ; D : (E|F) ; C -> !E; )
fm2 = FM (I : J [K] L ; )
fm3 = FM (M : (N|O|P)+ ; )
cst = constraints (J implies N ; )
```

```
// equivalent to aggregate { fm1 fm2 fm3 }
```




```
fm4 = aggregate fm* withMapping cst
```

Previous
version

```
MacBook-Pro-de-Mathieu-2:FML-scripts macher$ java -jar -Xmx1024M ../FML-0.9.9.5.jar a
FAMILIAR (for FeAture Model sCrIpt Language for manIpulation and Automatic Reasoning)
University of Nice Sophia Antipolis, UMR CNRS 6070, I3S Laboratory
https://nyx.unice.fr/projects/familiar/
fml> cores fm4
res0: (SET) {C;fm4;A;J;I;B;L;M}
fml> falseOptionals fm4
res1: (SET) {F;C}
fml> operator fm4.C
res2: (VARIABILITY_OPERATOR) OPTIONAL
fml> operator fm4.F
res3: (VARIABILITY_OPERATOR) ALTERNATIVE
fml> sibling fm4.F
res4: (SET) {E}
fml> deads fm4
res5: (SET) {E}
fml> operator fm4.E
res6: (VARIABILITY_OPERATOR) ALTERNATIVE
fml> fm4
fm4: (FEATURE_MODEL) fm4: A I M ;
A: [D] B [C] ;
I: J L [K] ;
M: (P|N|O)+ ;
D: (E|F) ;
(C -> !E);
(J -> C);
```



Merging Feature Models



```
fmsupp1 = FM (MedicalImage : [Anonymized] MRI [DICOM] ; MRI : (T1|T2) ; )
fmsupp2 = FM (MedicalImage : Anonymized MRI [Header] ; MRI : [T1] [T2] ; )
fmsupp3 = FM (MedicalImage : [Anonymized] MRI [DICOM] ; MRI : [T1] [T2] ; T1 -> Anonymized; )
```



```
s1 = configs fmsupp1
s2 = configs fmsupp2
s3 = configs fmsupp3
```

```
s123 = setUnion s3 setUnion s1 s2
```

```
fmSupp = merge sunion fmsupp*
```

```
assert (size s123 eq counting fmSupp)
```

```
fmCommon = merge intersection { fmsupp1 fmsupp2 }
sC = configs fmCommon
sC2 = setIntersection s1 s2
```





Comparing Feature Models

```
fm0 = FM (A: (B|C) ; )
fm1 = FM (A: (B|C)+ ; )
```

c
a
c




```
MacBook-Pro-de-Mathieu-2:FML-scripts macher$ java -jar -Xmx1024M ../FML-0.9.9.5.jar
FAMILIAR (for FeAture Model sCrIpT Language for manIpulation and Automatic Reasoning)
University of Nice Sophia Antipolis, UMR CNRS 6070, I3S Laboratory
https://nyx.unice.fr/projects/familiar/
fml> cmp23
cmp23: (STRING) REFACTORING
fml>
```



```
assert (cmp10 eq GENERALIZATION)
```


// example taken from Automated Analysis of Feature Models

```
fm2 = FM (A: B [C] [D]; )
fm3 = FM (A: B [C]; B : [D]; )
cmp23 = compare fm2 fm3
```



Putting all together: Example 1

Merge Intersection: Available Suppliers



In FAMILIAR


```
REGsupp1 = FM (Registration : Header Format Modality [Affine] ;
Header : (v1|v3);
Format : (DICOM|Nifti) ;
Modality : CT; )

REGsupp2 = FM (Registration : Header [Affine] Format Modality ;
Header : (v1|v2);

MacBook-Pro-de-Mathieu-2:FML-scripts macher$ java -jar -Xmx1024M ../FML-0.9.9.6.jar suppliersExample0.fml
FAMILIAR (for FeAture Model scrIPt Language for manIPulation and Automatic Reasoning) version 0.9.9.6 (beta)
University of Nice Sophia Antipolis, UMR CNRS 6070, I3S Laboratory
https://nyx.unice.fr/projects/familiar/
fml> ls
(FEATURE_MODEL) REGsupp3
(FEATURE_MODEL) REGsupp2p
(FEATURE_MODEL) REGrequired
(FEATURE_MODEL) REGsupp3p
(FEATURE_MODEL) REGsupp1p
(FEATURE_MODEL) REGsupp2
(FEATURE_MODEL) REGsupp1
fml> REGsupp3p
REGsupp3p: (FEATURE_MODEL) False
fml> REGsupp1p
REGsupp1p: (FEATURE_MODEL) Registration: Header Modality Format ;
Header: v1 ;
Modality: CT ;
Format: (DICOM|Nifti) ;

REGsupp1p = merge intersection { REGrequired REGsupp1 }
REGsupp2p = merge intersection { REGrequired REGsupp2 }
REGsupp3p = merge intersection { REGrequired REGsupp3 }
```

Merge Union: Availability Checking



In FAMILIAR

```

REGsupp1 = FM (Registration : Header Format Modality [Affine] ;
               Header : (v1|v3);
               Format : (DICOM|Nifti) ;
               Modality : CT; )

REGsupp2 = FM (Registration : Header [Affine] Format Modality ;
               Header : (v1|v2);
               Format : (Nifti|GE) ;
               Modality : MRI; )

REGsupp3 = FM (Registration : Header [Rigid] Format Modality ;
               Header : (v2|v3) ;
               Format : Nifti ;
               Modality : (MRI|PET); )




REGrequired = FM (Registration : Header Format Modality ;
                  Header : v1 ; //v3;
                  Format : (DICOM|Nifti) ;
                  Modality: (MRI|CT);
                  !DICOM or !MRI;
                  )

REGmspl = merge union REGsupp*           // merge all FMs whose variable identifier starts w.

cmp = compare REGrequired REGmspl
//missingSPL = merge diff { REGrequired REGmspl }

```

Merging operation: implementation issues



```

fmsupp1 = FM (MedicalImage : [Anonymized] MRI [DICOM] ; MRI : (T1|T2) ; )
fmsupp2 = FM (MedicalImage : Anonymized MRI [Header] ; MRI : [T1] [T2] ; )
fmsupp3 = FM (MedicalImage : [Anonymized] MRI [DICOM] ; MRI : [T1] [T2] ; T1 -> Anonymized; )

// computing the union of sets of configurations like this is COSTLY
s1 = configs fmsupp1
s2 = configs fmsupp2
s3 = configs fmsupp3

s123 = setUnion s3 setUnion s1 s2

// you WONT scale
//...

fmSupp = merge sunion fmsupp*

assert (size s123 eq counting fmSupp)
  
```

Anonymized v Header v DICOM v ~T1 v ~T2

Merging operation: semantic issues (2)

Φ

$s_0 = \{$

$\{MI, MA, F, CT, Nifti\},$


$\{MI, MA, F, CT, Nifti, AN\},$

$\{MI, MA, F, DICOM, MRI, AN\}$


$\}$

Union
Intersection


Diff



How to synthesise a feature model that represents the union of input sets of configurations?




(c) fm_1




(d) fm_2

Fig. 2: For a given set of configurations, three possible yet different FMs ($s_0 = \llbracket fm_0 \rrbracket = \llbracket fm_1 \rrbracket = \llbracket fm_2 \rrbracket$)


Merging operation: algorithm



Φ_1



Φ_2




Φ_3

Φ_{123}


merged propositional formula

+

How to synthesise a feature model that represents the union of input sets of configurations?



merged hierarchy



Set mandatory features
Detect Xor and Or-groups
Compute “implies/excludes” constraints

see also [Czarnecki SPLC'07 or SPLC'12]




Merging operation: back to hierarchy

fm1 = **FM** (A : B ; B : C ;)

fm2 = **FM** (A : B ; B : [C] ;)

fm3 = **FM** (A : [C] ; C : [B] ;)

fm4 = **merge sunion** { fm1 fm2 fm3 }



> configs fm4
res12: (SET) {{C;A};{A;B};{A};{A;B;C}}


?

Related Works

- Well-defined semantics
- Guarantee semantics properties by construction
- More compact feature models than reference-based techniques [Schobbens et al., 2007], [Hartmann et al., 2007]
 - Easier to understand
 - Easier to analyze (e.g., compare with another)
- Applicable to any propositional feature models
 - Full support of propositional constraints
 - Different hierarchies [Van Den Broek et al., SPLC'2010/2012]
- Syntactical strategies fail [Alves et al., 2006], [Segura et al., 2007]

Another Example

Problem: multiple „car models“



Problem: multiple „car models“

Model line	Body style	Model
● Audi A1 ● Audi A3 ● Audi A4 ● Audi A5 ● Audi A8	● Audi Q3 ● Audi Q5 ● Audi Q7 ● Audi TT ● Audi R8	● Saloon ● Avant ● 3 door ● Sportback ● Coupé ● Cabriolet ● Roadster ● Spyder ● allroad quattro ● SUV
		● A1 ● A1 Sportback ● A3 ● A3 Sportback ● A3 Cabriolet ● S3 Sportback ● RS 3 Sportback ● A4 Saloon ● A4 Avant ● A4 allroad quattro ● S4 Saloon ● S4 Avant ● A5 Coupé ● A5 Sportback ● A5 Cabriolet ● S5 Coupé ● S5 Sportback ● S5 Cabriolet ● RS 5 Coupé ● A8 ● A8L ● A8 W12 ● Q3 ● Q5 ● Q7 ● TT Coupé ● TT Roadster ● TTS Coupé ● TTS Roadster ● TT RS Coupé ● TT RS Roadster ● R8 Coupe ● R8 Spyder

Model line	Body style	Model
● Audi A1 ● Audi A3 ● Audi A4 ● Audi A5 ● Audi A8	● Audi Q3 ● Audi Q5 ● Audi Q7 ● Audi TT ● Audi R8	● 3 door ● Sportback ● Cabriolet
		● A3 ● A3 Sportback ● A3 Cabriolet ● S3 Sportback ● RS 3 Sportback

Problem: multiple „car models“

Model line	Body style	Model
☐ Audi A1 ☒ Audi A3 ☐ Audi A4 ☐ Audi A5 ☐ Audi A8	☐ 3 door ☐ Sportback	☐ A3 ☐ A3 Sportback ☐ A3 Cabriolet ☐ S3 Sportback ☐ RS 3 Sportback
☐ Audi Q3 ☐ Audi Q5 ☐ Audi Q7 ☐ Audi TT ☐ Audi R8	☐ Cabriolet	

Model line	Body style	Model
☐ Audi A1 ☐ Audi A3 ☒ Audi A4 ☐ Audi A5 ☐ Audi A8	☐ Saloon ☐ Avant	☐ A4 Saloon ☐ A4 Avant ☐ A4 allroad quattro ☐ S4 Saloon ☐ S4 Avant
☐ Audi Q3 ☐ Audi Q5 ☐ Audi Q7 ☐ Audi TT ☐ Audi R8	☐ allroad quattro	

Model line	Body style	Model
☒ Audi A1 ☐ Audi A3 ☐ Audi A4 ☐ Audi A5 ☐ Audi A8	☐ 3 door ☐ Sportback	☐ A1 ☐ A1 Sportback
☐ Audi Q3 ☐ Audi Q5 ☐ Audi Q7 ☐ Audi TT ☐ Audi R8		

Problem: multiple „car models“

Model line	Body style	Model
● Audi A1 ● Audi A3 ● Audi A4 ● Audi A5 ● Audi A8	● Saloon ● Avant ● 3 door ● Sportback ● Coupé	● Cabriolet ● Roadster ● Spyder ● allroad quattro ● SUV
● Audi Q3 ● Audi Q5 ● Audi Q7 ● Audi TT ● Audi R8		● A1 ● A1 Sportback ● A3 ● A3 Sportback ● A3 Cabriolet ● S3 Sportback ● RS 3 Sportback ● A4 Saloon ● A4 Avant ● A4 allroad quattro ● S4 Saloon ● S4 Avant ● A5 Coupé ● A5 Sportback ● A5 Cabriolet ● S5 Coupé ● S5 Sportback
		● S5 Cabriolet ● RS 5 Coupé ● A8 ● A8L ● A8 W12 ● Q3 ● Q5 ● Q7 ● TT Coupé ● TT Roadster ● TTS Coupé ● TTS Roadster ● TT RS Coupé ● TT RS Roadster ● R8 Coupe ● R8 Spyder

#1 – top-down: specify constraints (e.g., excludes) of all model lines upfront

Two modeling approaches

#2 – bottom-up: elaborate a feature model for each model line and merge them

Model line	Body style	Model
● Audi A1 ● Audi A3 ● Audi A4 ● Audi A5 ● Audi A8	● 3 door ● Sportback	● A3 ● A3 Sportback ● A3 Cabriolet ● S3 Sportback ● RS 3 Sportback
● Audi Q3 ● Audi Q5 ● Audi Q7 ● Audi TT ● Audi R8		

Model line	Body style	Model
● Audi A1 ● Audi A3 ● Audi A4 ● Audi A5 ● Audi A8	● Saloon ● Avant	● A4 Saloon ● A4 Avant ● A4 allroad quattro ● S4 Saloon ● S4 Avant
● Audi Q3 ● Audi Q5 ● Audi Q7 ● Audi TT ● Audi R8	● allroad quattro	

Model line	Body style	Model
● Audi A1 ● Audi A3 ● Audi A4 ● Audi A5 ● Audi A8	● 3 door ● Sportback	● A1 ● A1 Sportback
● Audi Q3 ● Audi Q5 ● Audi Q7 ● Audi TT ● Audi R8		

#1 top-down


Model line	Body style	Model						
- Audi A1 - Audi A3 - Audi A4 - Audi A5 - Audi Q3 - Audi Q5 - Audi Q7 - Audi TT	- Saloon - Avant 3 door - Sportback - Cabriolet - Roadster - Spyder - allroad quattro - SUV	- A1 - A1 Sportback - A3 - A3 Sportback - A3 Cabriolet - S3 Sportback - RS 3 Sportback - A4 Saloon - A4 Avant - A4 allroad quattro - S4 Saloon - S4 Avant - A5 Coupé - A5 Sportback - A5 Cabriolet - S5 Coupé - S5 Sportback - S5 Cabriolet - RS 5 Coupé - A8 - A8L - A8 W12 - Q3 - Q5 - Q7 - TT Coupé - TT Roadster - TTS Coupé - TTS Roadster - TT RS Coupé - TT RS Roadster - R8 Coupe - R8 Spyder						
<pre> ModelLine { group oneof { AudiA1 { AudiA1 -> (A1 A1Sportback); AudiA1 -> (Door3 Sportback); }, AudiA3 { AudiA3 -> (A3 A3Sportback A3Cabriolet S3 S3Sportback RS3Sportback); AudiA3 -> (Door3 Sportback Cabriolet); }, AudiA4 { AudiA4 -> (A4Saloon A4Avant A4AllroadQuattro S4Saloon S4Avant); AudiA4 -> (Saloon Avant AllroadQuattro); }, AudiA5 { AudiA5 -> (A5Coupé A5Sportback A5Cabriolet S5Coupé S5Sportback S5Cabriolet RS5Coupé); AudiA5 -> (Sportback Coupé Cabriolet); }, AudiA6 { AudiA6 -> (A6Saloon A6Avant); AudiA6 -> (Saloon Avant); }, }, } </pre>								
<table> <tr> <th>Model line</th><th>Body style</th><th>Model</th></tr> <tr> <td> - Audi A1 - Audi A3 - Audi A4 - Audi A5 - Audi A8 - Audi Q3 - Audi Q5 - Audi Q7 - Audi TT - Audi R8 </td><td> 3 door - Sportback - Cabriolet </td><td> - A3 - A3 Sportback - A3 Cabriolet - S3 Sportback - RS 3 Sportback </td></tr> </table>	Model line	Body style	Model	- Audi A1 - Audi A3 - Audi A4 - Audi A5 - Audi A8 - Audi Q3 - Audi Q5 - Audi Q7 - Audi TT - Audi R8	3 door - Sportback - Cabriolet	- A3 - A3 Sportback - A3 Cabriolet - S3 Sportback - RS 3 Sportback		
Model line	Body style	Model						
- Audi A1 - Audi A3 - Audi A4 - Audi A5 - Audi A8 - Audi Q3 - Audi Q5 - Audi Q7 - Audi TT - Audi R8	3 door - Sportback - Cabriolet	- A3 - A3 Sportback - A3 Cabriolet - S3 Sportback - RS 3 Sportback						
<table> <tr> <th>Model line</th><th>Body style</th><th>Model</th></tr> <tr> <td> - Audi A1 - Audi A3 - Audi A4 - Audi A5 - Audi A8 - Audi Q3 - Audi Q5 - Audi Q7 - Audi TT - Audi R8 </td><td> - Saloon - Avant - allroad quattro </td><td> - A4 Saloon - A4 Avant - A4 allroad quattro - S4 Saloon - S4 Avant </td></tr> </table>	Model line	Body style	Model	- Audi A1 - Audi A3 - Audi A4 - Audi A5 - Audi A8 - Audi Q3 - Audi Q5 - Audi Q7 - Audi TT - Audi R8	- Saloon - Avant - allroad quattro	- A4 Saloon - A4 Avant - A4 allroad quattro - S4 Saloon - S4 Avant		
Model line	Body style	Model						
- Audi A1 - Audi A3 - Audi A4 - Audi A5 - Audi A8 - Audi Q3 - Audi Q5 - Audi Q7 - Audi TT - Audi R8	- Saloon - Avant - allroad quattro	- A4 Saloon - A4 Avant - A4 allroad quattro - S4 Saloon - S4 Avant						
<table> <tr> <th>Model line</th><th>Body style</th><th>Model</th></tr> <tr> <td> - Audi A1 - Audi A3 - Audi A4 - Audi A5 - Audi A8 - Audi Q3 - Audi Q5 - Audi Q7 - Audi TT - Audi R8 </td><td> 3 door - Sportback </td><td> - A1 - A1 Sportback </td></tr> </table>	Model line	Body style	Model	- Audi A1 - Audi A3 - Audi A4 - Audi A5 - Audi A8 - Audi Q3 - Audi Q5 - Audi Q7 - Audi TT - Audi R8	3 door - Sportback	- A1 - A1 Sportback		
Model line	Body style	Model						
- Audi A1 - Audi A3 - Audi A4 - Audi A5 - Audi A8 - Audi Q3 - Audi Q5 - Audi Q7 - Audi TT - Audi R8	3 door - Sportback	- A1 - A1 Sportback						

```


BodyStyle {
  group oneof {
    Saloon
    {
      Saloon -> (A4Saloon || S4Saloon || A6Saloon || A8 || A8L || A8W12);
    },
    Avant
    {
      Avant -> (A4Avant || S4Avant || A6Avant);
    },
    Door3
    {
      Door3 -> (A1 || A3 || S3);
    },
    Sportback
    {
      Sportback -> (A1Sportback || A3Sportback || S3Sportback || RS3Sportback || A5Sportback || S5Sportback || A7Sportback);
    },
    Coupé
    {
      Coupé -> (A5Coupé || S5Coupé || RS5Coupé || TTCoupé || TTS Coupé || TTRS Coupé || R8Coupé);
    },
  },
}

```

#1 bottom-up



#1 bottom-up (FAMILIAR)




```

a fml> fmAudiS = merge union { fm1 fm2 fm3 }
a fmAudiS: (FEATURE_MODEL) Audi: ModellLine BodyStyle ;
F ModellLine: (A1|A4|A3) ;
L BodyStyle: (Saloon|Door3)? (Cabriolet|AllroadQuattro)? (Sportback|Avant)? ;
h
+ (A4 -> !Sportback);
+ (A1 -> !Avant);
M (A1 -> !Saloon);
E (A3 -> !Saloon);
+ (A4 -> !Cabriolet);
+ (A1 -> !AllroadQuattro);
M (A1 -> !Cabriolet);
E (A1 -> !Door3);
+ (A3 -> !Avant);
M (A3 -> !AllroadQuattro);
E

```

9.9.4 (beta)



Building “views” of a feature model

[illegible]

Building “views” of a feature model

- Problem: given a feature model, how to decompose it into smaller feature models?
- Semantics?
 - What’s the hierarchy
 - What’s the set of configurations?

A first try




Problem: You can select **A3** without **A5**


Hierarchy and Configuration matter!

Slicing Operator

slicing criterion : an arbitrary set of features, relevant for a feature model user





slice : a new feature model, representing a projected set of configurations



Slicing operator: going into details

projected set of configurations






fm1p = {
 {A,B,C,D,E,P,R,T,U,W},
 {A,B,C,E,P,S,T,U,W},
 {A,B,C,D,E,P,R,T,W},
 {A,B,C,E,P,S,T,W},
 {A,B,C,E,P,S,T,U,W},
 {A,B,C,E,P,S,T,V,W},
 {A,B,C,E,P,S,T,W},
 {A,B,C,D,E,P,R,T,W},
 } }

fm1p = {
 {D,E,T},
 {S,T},
 {D,E,T},
 {S,T},
 {S,T},
 {S,T},
 {D,E,T},
 }

Slicing operator: going into details


synthesizing the corresponding feature model



fm1p = {
 {**D,E,T**},
 {**S,T**}
 }

constraints

- E implies D
- D implies E



see also [Acher et al., ASE'11/AOSD'12]

Slicing operator with FAMILIAR (1)



```

fm1 = FM (W : P T [U] ; T : [V] A ;
           A : B C [D] ;
           C : [E] [F] ;
           P : (R|S)+ ;
           E implies D ; R implies E ;
           S implies (F and !E) ; D implies !F ; )

fm2 = slice fm1 including { S T E D }
fm2bis = slice fm1 excluding { W P R V A B C F U }

cmp = compare fm2 fm2bis
assert (cmp eq REFACTORING)

```



Slicing with FAMILIAR (2)

```

fm1 = FM (W : P T [U] ; T : [V] A ;
          A : B C [D] ;
          C : [E] [F] ;
          P : (R|S)+ ;
          E implies D ; R implies E ;

          S implies (F and !E) ; D implies !F ; )

fm2 = slice fm1 including fm1.A.* ++ { fm1.A }

fm3 = slice fm1 including fm1.P.* ++ { fm1.P }
//fm3bis = slice fm1 including { fm1.P fm1.R fm1.S } // equivalent to fm3

fm4 = slice fm1 including { fm1.E fm1.D fm1.F }

fts5 = { fm1.P fm1.W } ++ fm1.P.*
fm5 = slice fm1 including fts5

```

Revisiting Merge and Slice: AggregateMerge






Figure 7.10: Merge of three feature models, I_0 , I_1 and I_2 using the slicing operator



```
fml> compare fmSuppAggSlice fmSupp
res4: (STRING) REFACTORING
```





Putting all together: Example 2



*From marketing,
customers, product
management*





*From existing software
assets (technical variability)*



NEW KANGOO VAN RANGE

01 Preferences	02 Version	03 Equipment & options
< Previous Next >		
OPTIONS		
> COMFORT		
☒ Central storage console & armrest between seats	£50.00	
> DRIVING		
☐ Electric door mirrors	£0.00	
> SAFETY & SECURITY		
☒ ESC (Electronic Stability Control) with traction and understeer control	£200.00	






From marketing,
customers, product
management



usefulness

$V1 \Leftrightarrow f1$
 $V2 \Leftrightarrow f2$
 $V3 \Leftrightarrow f3$

realizability




From existing software assets




Realizability checking

1 aggregate



2 slice ("realizable part")



3 compare

4 merge diff ("unrealizable products")

$\{\{V1, V3, V2, VP1\},$
 $\{V1, VP1\},$
 $\{V3, VP1\},$
 $\{VP1\}\}$



With FAMILIAR

```
/*
 * Metzger et al. 2007, RE'07
 * Disambiguating the .....
 * Figure 1, Section 3
 */
```

```
fmSoftware = FM (R : (F1|F2) F3 [F4] ; )
```

```
MacBook-Pro-de-Mathieu-2:FML-scripts macher$ java -jar -Xmx1024M ../FML-0.9.9.6.jar realizability.fml
FAMILIAR (for FeAture Model scrIpt Language for manIpulation and Automatic Reasoning) version 0.9.9.6
University of Nice Sophia Antipolis, UMR CNRS 6070, I3S Laboratory
https://nyx.unice.fr/projects/familiar/
fml> ls
(FEATURE_MODEL) gFM
(FEATURE_MODEL) fmSoftware
(FEATURE_MODEL) fmPLDiff
(FEATURE_MODEL) fmPLPrime
(FEATURE_MODEL) fmPL
(SET) xLink
fml> configs fmPLDiff
res1: (SET) {{VP1;V1}};{{VP1;V3}};{{VP1}};{{V3;V1;VP1;V2}}
```


Model-based Variability Management:

Summary
What's next?

Summary

```
root PloneMeeting {
  group allof {
    General,
    Data,
    WorkflowSec,
    Interface,
    Email,
    Tasks,
    Advices,
    Votes
  }
}

General {
  group allof {
    Title ,
    opt DefaultAssembly,
    opt DefaultSignatures,
    LinkedFolder,
    opt IsDefault,
    NumberLastItemLastMeeting {
      int number;
    },
    opt NumberLastMeetingConfig {
      int number;
    },
    opt MeetingConfigID
  }
}
```




Text-based variability language with formal semantics & support (Boolean form)

A domain-specific language for Importing, exporting, editing, composing, decomposing, computing differences, comparing, reasoning about (multiple) feature models




What's next?

- Increasing further the adoption of the languages
 - You're the future users!
- TVL
 - Comprehensive support for non Boolean constructs
 - Satisfiability Modulo Theory (SMT) solver
- FAMILIAR
 - Applicability, Learnability, Expressiveness, Usability
- Connection of feature models to other artefacts
 - Automated product derivation
 - Verification & Certification



#1 Reverse Engineering Architectural Feature Models

Case Study: FraSCAti Architecture




[Acher et al., ECSA'11]
[Acher et al., BENEVOL'11]
[Acher et al., GDR GPL'12]

Collaboration with Anthony Cleve (University of Namur / PRECISE, Belgium),
Philippe Collet and Philippe Lahire (University of Nice Sophia Antipolis),
Philippe Merle and Laurence Duchien (University of Lille / INRIA)


Extraction process

**Software
Artefacts**





**Variability
Modeling**

**Software
Architect View**



Philippe Merle,
software architect of FraSCAti




**Automatic
Extraction**



Combination of plugin dependencies
and hierarchical component model to
synthesise a feature model

Highlights

- Automated Procedure
 - Extracting and Combining Variability Sources (incl. software architect knowledge)
 - Advanced feature modeling techniques have been developed (tool supported with FAMILIAR)
- Lessons Learned
 - Extraction procedure yields promising results
 - Essential role of software architect
 - To validate the extracted feature model
 - To integrate knowledge
- Ongoing Work
 - Evolution of FraSCAti (v1.3, v1.4, etc.)
 - Applicability to other software architectures





Identifier	License	Language	Storage	LicenseCostFee
Confluence	Commercial	Java	Database	US10
PBwiki	Nolimit	No	No	Yes
MoinMoin	GPL	Python	Files	No
DokuWiki	GPL2	PHP	Files	No
PmWiki	GPL2	PHP	Files	No
DrupalWiki	GPL2	PHP	Database	Different Licences
TWiki	GPL	Perl	FilesRCS	Community
MediaWiki	GPL	PHP	Database	No

```

- <features>
- <product p_id="1" name="DokuWiki">
- <general_info name="General Information">
- <info name="Description">
  DokuWiki is a standards compliant, simple to use Wiki, mainly aimed at creating documentation of any kind. It is a
  syntax which makes sure the datafiles remain readable outside the Wiki and eases the creation of structured texts. A
</info>
- <info name="Record added">2005-11-22</info>
- <info name="Last updated">2011-05-25</info>
- </general_info>
- <itemgroup g_id="1" name="General Features">
- <item i_id="11" name="Version">2011-05-25 "Rincewind"</item>
- <item i_id="60" name="Last Release Date">2011-05-25</item>
- <item i_id="2" name="Author">Andreas Gohr</item>
- <item i_id="3" name="URL">http://www.dokuwiki.org</item>
- <item i_id="4" name="Free and Open Source">Yes</item>
- <item i_id="5" name="License">GPL 2</item>
- <item i_id="51" name="Programming Language">PHP</item>
- <item i_id="123" name="Data Storage">Files</item>
- <item i_id="55" name="License Cost/ Fee">No</item>
- <item i_id="61" name="Development status">Mature</item>
- <item i_id="118" name="Intended Audience">private, small to medium companies</item>
- </itemgroup>
- <itemgroup g_id="18" name="Hosting Features">
- <item i_id="140" name="Storage Quota">Linux, UNIX, Windows, MacOS X, probably others</item>
- <item i_id="141" name="Bandwidth Quota">No</item>
- <item i_id="142" name="Other Limits">Apache, IIS, Lighttpd, anything with PHP support</item>
- <item i_id="146" name="Topic Restrictions">
- <item i_id="143" name="Corporate Branding">Yes</item>
- <item i_id="144" name="Own Domain">No</item>
  
```


#2 from product descriptions to feature models



Collaboration with Patrick Heymans, Anthony Cleve, Gilles Perrouin (University of Namur / PRECISE, Belgium), Philippe Collet and Philippe Lahire (University of Nice Sophia Antipolis),

Manual extraction of a feature model from product description(s) is not possible

Identifier	License	Language	Storage	LicenseCostFee	RSS	Unicode
Confluence	Commercial	Java	Database	US10	Yes	Yes
PBwiki	Nolimit	No	No	Yes	Yes	No
MoinMoin	GPL	Python	Files	No	Yes	Yes
DokuWiki	GPL2	PHP	Files	No	Yes	Yes
PmWiki	GPL2	PHP	Files	No	Yes	Yes
DrupalWiki	GPL2	PHP	Database	Different Licences	Yes	Yes
TWiki	GPL	Perl	FilesRCS	Community	Yes	Yes
MediaWiki	GPL	PHP	Database	No	Yes	Yes



Automation

- Each product description is encoded as a feature model

Identifier	License	Language	Storage	LicenseCostFee	RSS	Unicode
Confluence	Commercial	Java	Database	US10	Yes	Yes
PBwiki	Nolimit	No	No	Yes	Yes	No
MoinMoin	GPL	Python	Files	No	Yes	Yes
DokuWiki	GPL2	PHP	Files	No	Yes	Yes
PmWiki	GPL2	PHP	Files	No	Yes	Yes
DrupalWiki	GPL2	PHP	Database	Different Licences	Yes	Yes
TWiki	GPL	Perl	FilesRCS	Community	Yes	Yes
MediaWiki	GPL	PHP	Database	No	Yes	Yes

→ fm1
 → fm2
 → fm3
 → fm4
 → fm5
 → fm6
 → fm7
 → fm8


- Feature models {fm1, fm2,...,fm8} are **merged**

- Output: a new feature model


- Configuration: union of input sets of configurations
- Hierarchy: by default, we exploit the structure of the tabular data
 - Can be overridden by specific user directive

- VariCell

- DSL built on top of FAMILIAR



Feature Model Differences




Syntactic differences do not scale

see [Acher et al., CAiSE'12]

Modeling Variability From Requirements to Runtime

The case of video surveillance processing chains



large number of software configurations
for a large number of requirements

Adaptive systems

Contributions

- Separation of Concerns
 - Software variability is distinguished from requirements variability
- A systematic approach to specify and reason about variability of adaptive systems
 - Variability requirements are step-wised specified at design time
 - Some variability choices are kept for runtime adaptation (e.g., Day/Night)
 - Reduction of software configurations to be considered at runtime
- Reasoning operations
 - Consistency checking
 - “Reachability” property
 - for all valid requirements (e.g., contexts), there exists at least one valid software configuration
 - Specialization checking
 - Choices Propagation
- Language support
 - aggregate + slice + compare + editing facilities
 - Reuse of feature models and analysis procedures in 6 scenarios

